



Submittal Data Sheet

22-Ton VRV-IV Heat Pump Unit - 230V

RXYQ264TTJU

FEATURES

- Variable Refrigerant Temperature (VRT) control allows the VRV IV to deliver up to 28% of improvement in seasonal cooling efficiency compared to previous Daikin VRV heat pump systems
- Same product structure for 230V and 460V simplifies ordering
- The rated seasonal cooling efficiency has been improved by an average of 11% compared to VRV III
- Improved efficiency with IEER values now up to 28
- Larger capacity single modules ranging up to 14 tons and systems up to 34 tons allow for a more flexible system design
- New configurator software designed to simplify the commissioning and maintenance of the system
- Larger capacity single modules allow for opportunity to reduce electrical connections, piping connections and outdoor unit mounting fixtures
- System wide auto-climate adjustment technology to increase the energy efficiency
- All inverter compressors to increase the efficiency and avoid starting current inrush
- Assembled in the US to increase flexibility and reduce lead times
- Standard Limited Warranty: 10-year warranty on compressor and all parts

BENEFITS

- 3 row 7mm heat exchanger coil improves efficiency
- Inverter control board cooled by refrigerant to avoid influence from ambient temperatures
- Heat exchanger coil wraps around on all 4 sides of the unit to increase the surface area / efficiency
- Designed with reduced MOP to optimize installation cost
- Digital display on the unit for improved and faster configuration, commissioning, and trouble shooting.





Submittal Data Sheet

22-Ton VRV-IV Heat Pump Unit - 230V

RXYQ264TTJU

PERFORMANCE

| | | | |
|----------------------------------|---|--------------------------------------|---|
| Outdoor Unit Model No. | RXYQ264TTJU | Outdoor Unit Name: | 22-Ton VRV-IV Heat Pump Unit - 230V |
| Type: | Heat Pump | Unit Combination: | RXYQ120TTJU + RXYQ144TTJU |
| Rated Cooling Conditions: | Indoor (°F DB/WB): 80 / 67 Ambient (°F DB/WB): 95 / 75 | Rated Heating Conditions: | Indoor (°F DB/WB): 70 / 70 Ambient (°F DB/WB): 47 / 43 |
| Rated Piping Length(ft): | | | |
| Rated Height Difference (ft): | 0.00 | | |
| Rated Cooling Capacity (Btu/hr): | 251,000 | Rated Heating Capacity (Btu/hr): | 283,000 |
| Nom Cooling Capacity (Btu/hr): | | Nom Heating Capacity (Btu/hr): | |
| Cooling Input Power (kW): | 24.00 | Heating Input Power (kW): | 20.60 |
| EER (Non-Ducted/Ducted): | 10.90 / 10.50 | Heating COP (Non-Ducted/Ducted): | 3.3 / 3.4 |
| IEER (Non-Ducted/Ducted): | 20.30 / 19.30 | Heating COP 17F (Non-Ducted/Ducted): | 2.4 / 2.3 |

OUTDOOR UNIT DETAILS

| | | | |
|---------------------------------------|-------------------|----------------------------------|---------------|
| Power Supply (V/Hz/Ph): | 208-230 / 60 / 3 | Compressor Type | Inverter |
| Power Supply Connections: | L1, L2, L3 Ground | Capacity Control Range (%): | 20 - 100 |
| Min. Circuit Amps MCA (A): | 36.3+55.1 | Capacity Index Limit: | 132.0 - 343.0 |
| Max Overcurrent Protection (MOP) (A): | 45+60 | Airflow Rate (H) (CFM): | 6286+8228 |
| Max Starting Current MSC(A): | | Gas Pipe Connection (inch): | 1-3/8 |
| Rated Load Amps RLA(A): | 26.2+(16.7+16.7) | Liquid Pipe Connection (inch): | 3/4 |
| Dimensions (Height) (in): | 66-11/16 | H/L Pressure Connection (inch) | |
| Dimensions (Width) (in): | 97-6/8 | H/L Equalizing Connection (inch) | |
| Dimensions (Depth) (in): | 30-3/16 | Sound Pressure (H) (dBA): | 64 |
| Net Weight (lb): | 528+695 | Sound Power Level (dBA): | |
| | | Max. No. of Indoor Units: | 45 |



Submittal Data Sheet

22-Ton VRV-IV Heat Pump Unit - 230V
RXYQ264TTJU

SYSTEM DETAILS

| | | | |
|--|-----------|-----------------------------------|----------|
| Refrigerant Type: | R-410A | Cooling Operation Range (°F DB): | 23 - 122 |
| Holding Refrigerant Charge (lbs): | 22.9+18.1 | Heating Operation Range (°F WB): | -4 - 60 |
| Additional Charge (lb/ft): | | Max. Pipe Length (Vertical) (ft): | 295 |
| Pre-charge Piping (Length) (ft): | | Cooling Range w/Baffle (°F DB): | - |
| Max. Pipe Length (Total) (ft): | 540 | Heating Range w/Baffle (°F WB): | - |
| Max Height Separation (Ind to Ind ft): | 0 | | |

DIMENSIONAL DRAWING

